

THE BANK OF MYSORE, LIMITED, BANGALORE.

Notice is hereby given that the Share Transfer Books of the Bank, will be closed for 15 days from 3rd July 1937 to 17th July 1937, both days inclusive.

BANGALORE,
2nd July 1937.

T. M. S. SUBRAMANIAM,
Ag. Manager.

"I intend moving the Hon'ble High Court of Mysore, Bangalore, to enrol me as an Advocate thereof."

K. SUBBIAH SETTY, B.A., B.L.

"I intend moving the Honourable High Court of Mysore at Bangalore, to enrol me as an Advocate thereof."

M. GOVINDA REDDY, M.A., LL.B.

"I intend moving the Hon'ble High Court of Mysore, to enrol me an Advocate thereof".

S. K. SUBBA RAO, B.A., LL.B.

NOTICE.

The Mysore Government Promissory Note No. D013575 of the 6½ per cent loan of 1940 for Rs. 100 originally standing in the name of *The Bank of Mysore, Ltd.*, and last endorsed to L. D. Seenappa, Lingadahalli, Tarikere Taluk, the Proprietor by whom it was never endorsed to any other person, a portion of which (bond) having been lost, notice is hereby given that application is about to be made to the Comptroller to the Government of His Highness, the Maharaja of Mysore for issue of a duplicate in favour of the proprietor. The public are cautioned against purchasing or otherwise dealing with the above mentioned security.

6-6-1937.

L. D. SEENAPPA.

GOVERNMENT OF MYSORE STORES PURCHASE COMMITTEE, BANGALORE.

No. S. P. C. 25117-52, dated 30th June 1937.

To

The Firms dealing in Machinery.

Enquiry No. 2357.

MACHINERY REQUIRED FOR M.P.L. AND SIVASAMUDRAM WORKSHOPS, E.D. 465.

GENTLEMEN,

I write to request you to quote your best prices and earliest time of delivery for the machinery described below:—

1. One—30" Upright Drilling Machine, double geared, and having self-acting feed, with automatic trip motion; hand feed by worm and wheel and rack, and also sensitive feed by hand-wheel operating direct on the rack and pinion shaft. The spindle should be balanced and the sleeve graduated. The table should be capable of swinging aside on pillar and being raised and lowered by screw and handle. Self-contained countershaft should be provided and the spindles should be bored for No. 4 Morse Taper.

It should also conform more or less to the following specifications:—

The machine should drill up to	1½ inch.
Diameter of spindle	1¼ "
Vertical adjustment of spindle	8 inches.
Vertical adjustment of table	19 "
Diameter of table	26 "
Driving pulleys	14×3½ inch.
Speed of pulley	300 revolutions.
Cone pulleys	11½ to 5½×2½ inch.
Diameter of turned column	7¼ inch.

2. One—Standard Planing Machine 4'×2'×2' (complete with one set of necessary tools) with machine-cut gearing and mild-steel pinions wherever necessary. The horizontal, vertical and angular feeds should be self-acting and the V bearings should have self-acting lubricators. The table should have a quick return.

The price to be quoted should be for delivery f.o.r., Mysore.